

PROTECTIVE COATING





- WATER BASED
- ✓ ECO-FRIENDLY, LOW VOC
- MAXIMUM HEAT TRANSFER RATE
- 10,000 HOUR RATING, ASTM B-117
- **✓ FDA 175.300 ACCEPTED**

MAXIMUM PROTECTION

- Corrosion Resistant
- · Abrasion Resistant
- Flexible for Clean-ability

ONE-STOP SHOP FOR COILS AND COATING

Excellent for Harsh, Salt-Air and High Wind Environments










HIGH QUALITY COILS WITH PROTECTIVE COATINGS IDEAL FOR HARSH ENVIRONMENTS



- Desalination plants
- Data Centers
- High Wind and Salt Environments
- Coastal and Offshore
- Refineries







Industries We Serve

- Food Processing and Storage
- HVAC/R
- Water Treatment
- Breweries
- Paper Mills
- Meat Processing
- Automotive
- Power Plants
- Industrial
- Mining
- Any Corrosive Environment

COMPARISON OF COATINGS

Criteria	DirectCoil AA Coating	E Coating	Heresite P-413
Salt Spray Corrosion ASTM B117	10,000 Hours	6,048 Hours	6,000 Hours
Modified Salt Spray ASTM G85	3,000 Hours	2,000 Hours	1,000 Hours
Humidity ASTM D-2247	2,000 Hours	1,000 (ASTM D1735)	2,000H ours
Cross-hatch ASTM D-3359	5B	5B	5B
Abrasion Resistance	1,000 cycles	Not Published	1,000 cycles
Material Color	Black	Black	Brown
Environmentally Friendly	Yes	No	No
VOC Content (lb./gal)	0.076	Not Published	2.25
UV Resistance	Yes	Additional Cost	No
Heat Conductive	Yes	No	No



CERTIFICATE OF COMPLIANCE

THE MANUFACTURER AND INDEPENDENT TEST LABORATORY WITNESS THAT AQUA AERO ANTI CORROSION COATINGS HAVE PASSED THE ACCELERATED TESTS AS DESCRIBED BELOW:



MANUFACTURER: DERCOM BV, BEUNINGEN NETHERLANDS, signs for manufacturing specifications.

MANUFACTURER: **DERCOM BV**, BEUNINGEN NETHERLANDS, signs for manufacturing specs

MANUFACTURING FACILITY CERTIFIED BY ISO 9001, certificate # QSC 296 AND ISO 14001, certificate # ESC 114, issued by BSI Quality

Systems

By Fred Derks, Technical Director



JETT Tadomawag 40

By Ben Alblas, COT Laboratory Managersalem 101: +31(0) 23 - 53 19 344
Fax: +31(0) 23 - 52 77 229





DirectCoil Protective Coating - Aluminum, 25 um and 1 mil			
ASTM B-117	10,000 Hours		
ASTM G-85, Annex 5	3,000 Hours		
Kesternich SFW 2, 0 S	40 Cycles		
Cycle Exchange, ISO 20340	1,000 Hours		
Taber Abraser	1,000 Cycles		
Flexibility, ISO 1519	PASSED*		
Humidity, ASTM D 2247	2,000 Hours		
Abrasion B 3359	G0/5B		
Pencil Hardness, BH	PASSED*		
Impact, 100lb./sq.in. ASTM 2794	PASSED*		
Sea Water Immersion, 110 Hours	PASSED*		
Mandrel Bend, 1/8" ASTM D522/93A	PASSED*		
Heat Resistance, 360°C for 4 Hours	PASSED*		
Cold Resistance, -42°C for 9 Days	PASSED*		
* Manufacturers Specification			

ONE-STOP-SHOP

FOR HIGH QUALITY COILS and PROTECTIVE COATING





A SINGLE SOURCE FOR ALL YOUR COIL NEEDS AND CUSTOM ENGINEERED HEAT TRANSFER PRODUCTS



5055 Taylor Kidd Boulevard Millhaven, Ontario KOH 1GO P 613.544.2200 F 613.544.7779 www.directcoil.com





